



Winkelprofil Nr. 162, 24,5 x 20 mm

- Aluminium.
- Versenkte Schraublöcher.

Werkstoff:	EN AW 6063 (DIN EN 573)
Werkstoffzustand:	T6 (DIN EN 755-2)
Vorbehandlung:	E6 (DIN EN 17 611)
Schichtdicke Eloxal:	Klasse 15 (DIN EN 17 611)

Zubehör: Befestigungsmaterial.
Geeignet für: Designbelag / LVT Click und Loose Lay, Designbelag / LVT Dryback, Textile und elastische Bodenbeläge, Laminat / Multilayer
Montageart: Schrauben

Winkelprofile sind ideal geeignet als kleiner Treppenwinkel, als Türschwellenprofil oder als Abschluss an Podesten. Sie schützen die Kanten des Bodenbelags dauerhaft.



Angle edge no. 162, 24.5 x 20 mm

- Aluminium.
- Countersunk holes.

Material:	EN AW 6063 (DIN EN 573)
Material condition:	T6 (DIN EN 755-2)
Pre-treatment:	E6 (DIN EN 17 611)
Thickness of anodised layer:	Class 15 (DIN EN 17 611)

Accessories: Fastening material.
Suitable for: Design flooring / LVT click and loose lay, Design flooring / LVT dryback, Textile and elastic floor coverings, Laminate / multilayer
Installation: screwing

Angle edges are ideally suited as a small staircase angle, as a door threshold profile or as a termination on platforms. They protect the edges of the flooring permanently.