

Übergangprofil Nr. 119, 100 mm


Übergangprofile schaffen Übergänge zwischen nahezu beliebigen, gleichhohen Bodenbelägen.

Die in verschiedensten Breiten, Formen, Materialien und Farben erhältlichen Profile lassen sich schnell und unkompliziert verlegen.

- Aluminium.
- Mittig versenkt gebohrt.

Werkstoff: EN AW 6063 (DIN EN 573)
Werkstoffzustand: T6 (DIN EN 755-2)
Vorbehandlung: E6 (DIN EN 17 611)
Schichtdicke Eloxal: Klasse 15 (DIN EN 17 611)

Zubehör: Befestigungsmaterial, farblich passend.
Geeignet für: Elastische Bodenbeläge, Textile Bodenbeläge
Montageart: Schrauben
Längen: 500 / 270 / 100 cm
Farbauswahl: silber, Edelstahl matt



Connection section no. 119, 100 mm

Connection sections create transitions between almost any level of flooring.

The profiles are available in a wide range of shapes, materials and colors and can be laid quickly and easily.

- Aluminium.
- Centre countersunk holes.

Material: EN AW 6063 (DIN EN 573)
Material condition: T6 (DIN EN 755-2)
Pre-treatment: E6 (DIN EN 17 611)
Thickness of anodised layer: Class 15 (DIN EN 17 611)

Accessories: Fastening material in matching colors.
Suitable for: elastic floor coverings, textile floor coverings
Installation: screwing
Lengths: 500 / 270 / 100 cm
Colours: silver, stainless steel matt